NO PEREMPTORY EXAMPLES FOR SIMPLIFY THE USE OF BESTGRIP'S NAILS

	1000	1100	1200	1300	1350	1400	1500	1600	1700	1750	1800	1800R	1900	1900R	3000A	3000B	3000C	3300
														Racing Svezia omologato				
MAGNETIC KEY with hexagonal attack of 1/8" use driver use manual	4000	4100	4200	4300	4300	4400	4500	4600	4700	4700	4800	4800	4900	4900				
MAGNETIC KEY with fixed manual handle															3200 	3200	3200	3500
DIMENSIONS diameter length	6x8	7.9x9.8	9x12.6	9x15.2	9x14.4	9x16.2	9x17.5	7.7x16.6	9x20.8	7.7x20.9	9x23.3	9x24.5	9x20.5	9x20	7.9x15.1	7.9x12.2	9x16	8.6x13.2
PROMINENCE (mm)	2.2	1.9	1.9	3.2	2.4	2.7	4	3.6	7.3	6.9	6.8	8	4	4.5/6.5	4.4	4.3	4.5	1
NAIL PENETRATION INTO THE RUBBER (mm)	5.8	7.9	10.7	12	12	13.5	13.5	13	13.5	14	16.5	16.5	16.5	13.5/15.5	10.7	7.9	11.5	12.2
MINIMUM TREAD Generically measures (mm)	5	5.9	8.5	9.5	9.5	11	11	10.5	11	11.5	14	14	14	10.5/12.5				
TIP SIZE (Ø mm)	1.7	2.2	2.6	2.6	2.6	2.6	2.6	2.6	2.2	2.2	2.6	2.6	2.6	2.6	1.7	1.7	1.7	2.6
ON ROAD CAR TYRE ANTI – SNOW		B-C H=5 l=40	A-B-C H=7.5 l=40		A-B-C H=9 l=40													
JEEP TYRE ANTI – SNOW TYRE OFF ROAD		B-C H=5 l=40	A-B-C H=7.5 l=40	A-B H=9 l=60	A-B-C H=9 l=40	A-B-C H=10.5 l=40	A-B H=10.5 l=40				A H=13.5 l=70		A-B H=13.5 l=70					
SAFETY SCHOOL DRIVES TYRE ANTI – SNOW TYRE OFF ROAD			H=7.5 l=70	H=9 D-E l=70	H=9 F-G l=70	H=10.5 l=70	H=10.5 l=70						H=13.5 l=70					
ON ROAD MOTORCYCLE ON ROAD TYRE OFF ROAD TYRE	B-C H=3 D l=40	B-C H=5 l=40	A-B-C H=7.5 l=40	A-B-C H=9 l=40	A-B-C H=9 l=40	A-B-C H=10.5 l=40	A-B H=10.5 l=40											
MOTORCYCLE ENDURO CROSS RACING									A H=10.5 D l=200	A H=11 D l=200		A H=14 G l=200						
MOTORCYCLE ENDURO CROSS TRAINING OFF – ROAD						B-C H=10.5 G l=60	A-B-C H=10.5 G l=60	A-B-C H=10 D l=60	A H=10.5 D l=100	A H=11 D l=100	A H=14 G l=100		A-B-C H=14 G l=60					
SUPERMOTARD SPECIAL EVENTS OFF ROAD TYRE							A-B H=10.5 l=150		A H=10.5 l=150	A H=11 D l=150	A H=14 G l=150	A H=14 G l=150						
QUAD			B-C H=7.5 D l=40	A-B-C H=9 l=40	B-C H=9 l=40	A-B-C H=10.5 l=40	A-B H=10.5 l=40				A H=14 l=40		A-B H=14 l=40					
MOUNTAINBIKE	A-B-C H=5 l=30																	
RALLY CAR TYRE RACING ICE						A-B-C H=10.5 l=100	A-B H=10.5 l=100				A H=12 l=100		A-B H=12 l=100	A/A-B H=10/12 l=100				
RALLY CAR TYRE RACING ROAD TYRE ANTI - SNOW		B-C H=5 l=40	A-B-C H=7.5 l=40	A-B H=9 l=40	A-B-C H=9 l=40	A-B-C H=10.5 l=40												
TRACTORS OPERATIVE CARS						A-B-C H=9 l=60	A-B H=9 l=60						A-B H=13 l=60					
TRUCK OPERATIVE CARS			A-B-C H=7 l=60		A-B-C H=8.5 l=60	A-B-C H=10 l=60												
TRACKS MINIM. PLUG DIAMETER 8mm								A-B-C H=13 l=100		A H=14 l=100								
TRACKS MINIM. PLUG DIAMETER 10mm						A-B-C H=13.5 l=100	A-B-C H=13.5 l=100	A-B-C H=13 l=100			A H=16.5 l=100		A-B-C H=16.5 l=100					
GO-KART TYRE OFF – ROAD PLUGGED			H=8 l=40	H=10 l=40	H=10 l=40	H=12 l=40	H=12 l=40											
ANTISLIP SHOES FOR HORSE								A-B-C H=12 l=8		A H=13 l=8								
ANTISLIP SHOES SPORT FREE TIME JOB Art. 3000 = 20 nails (8 art. 3000 a for heel 12 art. 3000 b for front sole) + 1 KEY Art. 3100 = 10 nails (4 art. 3000 a for hell 6 art. 3000 b for front sole)															A-B-C H=10.7 l=10	A-B-C H=8 l=10		
ANTISLIP SHOES FOR SPORTING FISHING Special for sole in felt or plugs large and thick in rubber																	A-B-C H=11.5 l=10	
ANTI-CONSUMPTION SHOES SUPERMOTARD BOOTS														NO YES				H=9 l=7

DISPOSITION OF THE NAILS ON THE TYRES

1) prepare in equidistant and in constant way the nails on the circumference of the tyre
2) don't prepare never the nails in single file, but in irregular and orderly way with a logic that must be followed on the whole circumference of the tyre
3) if the tyre is used also in roads without snow it is better putting only the nails along the sides on the front tyres

A=MUCH SNOW / B=LITTLE SNOW / C=WITHOUT SNOW / D=FRONT TYRE WITHOUT TRACTION / E=REAR TYRE WITHOUT TRACTION / F=FRONT TYRE WITH TRACTION G=REAR TYRE WITH TRACTION / H=MINIMUM TREAD / I=MINIMUM QUANTITY IN EVERY WHEEL OR FOOTWEAR

All the measures are express in millimeters

ATTENTION! for the use of the nails always follow to the normative in force in your own country. bestgrip dissolves from all liability to misuse the products